EPSON
EXCEED YOUR VISION

PT. MANDIRI ARTHA SOLUSI
EMPOWERING BUSINESS FORWARD

LARGE FORMAT PRINTER
SURECOLOR™ SC-F6330/F7270

DESIGNED FOR PERFORMANCE, PURPOSED FOR AFFORDABILITY.

Sleeker, faster, higher performance. Epson SureColor F-Series printers include some of the latest advancements in printing technology to deliver amazing performance at an affordable running costs. With a fresh, stylish look in black, the SC-F6330 turns any office into a modern space. The SC-F7270 is designed for roll-based production, ideal for short to medium-volume roll-to-roll custom fabric, textile and soft signage. Developed with printing technology synonymous with Epson, both the SC-F6330 and SC-F7270 uses PrecisionCore™ TFP® printhead and UltraChrome DS ink in bigger ink pack capacities for increased productivity and higher quality printing of custom clothing, soft signage, merchandise and hard surface work.

Up to 64" Wide* | 1.5L Ink Tanks | 1 Year Warranty | Environmentally Friendly

4 COLOURS		DS	MAXIMUM MEDIA WIDTH	MAX. INK CAPACITY PER COLOUR	RIP INCLUDED	PRINT SPEEDS** SQM/HR		
						MAX SPEED	PRODUCTION	HIGH QUALITY
	SC-F6330	EPSON ULTRACHROME DYE SUB INK	44"	1.5 L		63,4	22,7	8,3
	SC-F7270		64"			58,9	22,2	8,2

SC-F6330
44" Wide Dye-Sub

SC-F7270
64" Wide Roll-to-Roll Dye-Sub

SC-F6330
High capacity 1.1L ink packs

SC-F7270
High capacity 1L ink packs



IT'S IN THE DETAILS.

With Epson UltraChrome™ ink, the SureColor SC-F6330/SC-F7270 delivers consistent, vibrant prints.

Remarkable Productivity
Deliver superior print quality, speed and reliability during continuous operation, with minimal downtime through Epson's advanced PrecisionCore printhead.

Affordable Prints with Peace of Mind
Cost-effective 1.1L/1L*** ink packs and new high-density black ink ensure lower ink usage and overall printing costs.

Consistent Vibrant Quality
UltraChrome DS ink is specially formulated to produce vibrant colours, intense blacks, sharp contours and smooth gradations.

PRECISIONCORE | EPSON ULTRACHROME DS INK | Epson Edge Print

*Up to 64" wide for F7270, 44" for SC-F6330
**All speed is dependent on RIP used
***1L ink packs are for use with SC-F7270 and 1.1L ink packs are for use with SC-F6330

SPECIFICATIONS
SURECOLOR™ SC-F6330/F7270

EPSON
EXCEED YOUR VISION

Model Number			SC-F6330	SC-F7270
Printer Width			44”	64”
Printing Technology				
Print Method			PrecisionCore™ TFP® Printhead	
Nozzle Configuration			360 nozzles x 4 channels x 1 head	360 x 2 nozzles each colour (x4)
Maximum Resolution			720 x 1440 dpi	
Print Modes	**Resolution**	**Pass**	**Print Speed (m²/h)**	
Draft	360 x 720	1	63.4	58.9
High Speed	720 x 720	2	30.4	30.3
Production	720 x 720	3	22.7	22.2
Production	720 x 720	4	15.8	16.2
High Quality	720 x 720	6	11.2	11.1
High Quality	720 x 1440	8	8.3	8.2
Ink System				
Ink Type			Epson UltraChrome™ DS dye-sublimation ink	
Colours			4 colours - Cyan, Magenta, Yellow, High-Density Black	
Ink Tank Capacity			1.5L	
Ink Pack Capacity			1.1L	1L
Paper Handling				
Paper Feed Method			Rear roll feed (2” / 3” core with max 150mm diameter); Auto take-up reel support over 914.4 mm (36”)	Rear roll feed (2” / 3” core with max 250mm diameter); Auto take-up reel unit
Media Width			300.0 mm (11.8”) to 1117.6 mm (44”)	300 to 1625.6mm
Printing Width (Margin)			Max. 1112mm Side Margin: 3mm both sides	Max. 1615.6mm Side Margin: 5mm both sides (10mm when using Media Holding Plates)
Media Thickness			Up to 1mm (over 75gsm)	0.08 - 1mm (over 75gsm)
Heat Press Condition				
Transfer Condition			Heater	
Temperature			200°C	
Time			40 sec	
Control Panel				
Colour & Size			2.7 inch colour LCD	2.5 inch colour LCD
Connectivity				
Standard			Hi-Speed USB, 100BASE-TX /1000BASE-T	
Ethernet			10BASE-T / 100BASE-TX / 1000BASE-T	
Memory				
Main			512MB	
Network			128MB	
Printer Software			Communication Driver, User’s Guide, EPSON LFP Remote Panel 2, EpsonNet Setup, EpsonNet Config, EpsonNet Pvrint, Wasatch SoftRIP	
Electrical Specifications				
Rated Voltage			AC 100 – 240V	
Rated Frequency			50 – 60Hz	
Power Supply			1.0 - 0.5A	10 - 5A
Power Consumption				
	Operating		Approx. 65W	Approx. 460W
	Standby		Approx. 20W	Approx. 30W w/ heater OFF
	Sleep		Approx. 3W	Approx. 10W
	Power Off		Less than 0.4W	Less than 0.6W
Recommended Operating Temperature & Humidity			15 - 35°C; 20 - 80% RH (non-condensation)	
Bundled Items				
Ink Supply System and Waste Ink Bottle Kit			C12C932491	-
Substrate Support System and Ink Supply System			-	C12C932471
Initial Ink Pack Set			C12C934741	C12C932111
Auto Take Up Reel			C12C934671	-
Roll Adaptor			C12C934701	-
Optional			**Order Code**	**Order Code**
Auto Cutter Blade			C13S902006	-
Media Holding Plate			-	C12C932121
Maintenance Kit			C13S210042	C13S210038
Waste Ink Bottle			C13T724000	C13T724000
Roll Media Adapter			C12C811391	-

Dimensions & Weight
SC-F6330
Weight: 94kg (without ink)

Ink Pack Compatibility
1.1L Ink Packs

● High Density Black	C13T46H800
● Cyan	C13T46H200
● Magenta	C13T46H300
● Yellow	C13T46H400

SC-F7270
Weight: 274kg (without ink)

Ink Pack Compatibility
1L Ink Packs

● High Density Black	C13T741X00
● Cyan	C13T741200
● Magenta	C13T741300
● Yellow	C13T741400

OEKO-TEX®
CONFIDENCE IN TEXTILES
ECO PASSPORT
NEP 1603 Nissenken
Textile chemicals. Tested and verified.
www.oeko-tex.com/ecopassport

©2019 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer’s Stamp

Contact Us.

Head Office. Ruko Sampoerna Square No. 15
Jl. Raya Hankam, Jatisampurna - Bekasi 17433
Telp. (021) 22813394

www.mandiriarthasolusi.co.id
info@mandiriarthasolusi.co.id

Mandiri Artha Solusi
@mandiriartha
mandiriartha
Mandiri Artha Solusi