



Key **Features**

All-in-One Solution | Powerful Embedded SoC Platform | Multi-Panel


Modular Design for Easy Installation | Vivid Colors and Stunning Images
| AV Control System Compatible




Product **Description**

The ViewSonic® LD135-151 is a premium all-in-one direct view LED commercial display. With a huge 135" screen size, the LD135-151 is built to impress as a centerpiece in any conference room, boardroom, or lobby. Along with its immense screen size, this display delivers stunning visuals with Full HD resolution, 1.5mm fine pixel pitch, 600-nit high brightness, 4,440Hz ultra-fast refresh rate, and 120% Rec.709 wide color gamut. Integrated ViewBoard® Cast screen sharing software* (along with optional ViewSonic vCastSender app), enables both on-site and online attendees to participate in video conferences and simultaneously share content. Equipped with twin dual-core processors, 4GB RAM, and 32GB of internal memory, the LD135-151 can play multimedia from internal storage or a USB flash drive 24 hours a day, seven days a week. And with remote configuration and content management system support, the ViewSonic LD135-151 is also suitable for a wide array of diverse signage applications.

*Chrome, Android, Windows, Mac OS, and iOS compliant











600-nit **BRIGHTNESS**

24/7



Display:

Display Type: Direct View LED

Display Size (in.): 135 Viewable Area (in.): 135

Light Source: Fine Pixel Pitch LED

LED Pitch Size (mm): 1.56 LED Grayscale: 14 bits 1920 x 1080 Resolution: Refresh Rate (Hz): 4,440 Aspect Ratio: 16:9 6,000:1 Static Contrast Ratio: Backlight Life (Hours): 100,000

Brightness: 600-nit Viewing Angles: 160° horizontal, 160° vertical

Operation Rating: 24/7

Networking:

802.11ac (2.4GHz/5GHz) Wifi:

Embedded Player:

OS: Android 8.0 Media Player Type: Yes

GPU: Mult-core MaliG51 MP2

CPU: Hi3751 V811 4GB DDR4 Memory:

Storage: 32GB (26GB available)

Audio:

Internal Speakers: 5W (x2)

Connector:

HDMI In(2), HDMI 1.4 Out (with HDCP 1.4)(1), HDMI 1.4 Out(1), 3.5mm Audio Out(1), USB 3.0(1), USB 2.0(2), USB 2.0 Type B(1), RS232(1), Ethernet LAN (RJ45)(1), IR in(1)

Power:

Voltage: 100-120V+/- 10%, 50/60Hz, 30A

Consumption (max): 2,900W 2,030W Consumption (typical): Stand-by: < 0.5 W

Controls:

On Screen Display: Yes Remote Control: Yes

Operating Conditions:

Temperature: 32-104° F (0 - 40° C)

Humidity (non-condensing): 20-80%

Weight (imperial):

Net (lbs): 297.6 Gross (lbs): 529.1

Weight (metric):

Net (kg): 135.0 Gross (kg): 240.0 Dimensions (imperial) (WxHxD):

70.9 x 29.3 x 33.5 Packaging (in.): Physical (in.): 118.9 x 71.1 x 1.4

Dimensions (metric) (WxHxD):

Packaging (mm): 1800 x 745.0 x 850.0 Physical (mm): 3020.9 x 1805.9 x 35.0

General:

AV Control: AMX Certified, Crestron Certified, Extron Certified Warranty: 5-year limited warranty on parts and labor, on-site service

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: Power Cord, Remote Control, QSG, Wall-mount x 1, Maintenance Tool (LD-MK-001) x 1, Spare Modules (LED PCB x 2)

Regulations: cTUVus, FCC, RoHS, Mexico CoC, Mexico Energy

UPC: 766907008784

Accessories:

LD-MK-001, LD-STND-001, NMP520-W, NMP520-WX, NMP660, SW-090, SW-091, SW-092, SW-093, SW-094, SW-095, SW-096, VB-CAM-001

Copyright © ViewSonic Corporation 2000-2021. All rights reserved. (07/22/2021 02:50 AM PST)

Contact Us.

Ruko Sampoerna Square No.15, Jl. Raya Hankam, Jatiraden, Jatisampurna, Bekasi 17433 Telp. (021) 22813394 - info@mandiriarthasolusi.co.id - www.mandiriarthasolusi.co.id

Branch Office.

Ruko Derwati Mas Estate, No. 31, Jl. Derwati Raya, Kel. Derwati, Kec. Rancasari - Bandung 40292 Telp. (022) 87311487

Follow Us.





