



Key **Features**

All-in-One Solution | Powerful Embedded SoC Platform | Multi-Panel

Modular Design for Easy Installation | Vivid Colors and Stunning Images

| AV Control System Compatible




BESTOF SHOW InfoComm

Product **Description**


The ViewSonic® LD163-181 is a premium all-in-one direct view LED commercial display. With a huge 163" screen size, the LD163-181 is built to impress as a centerpiece in any conference room, boardroom, or lobby. Along with its immense screen size, this display delivers stunning visuals with Full HD resolution, 1.8mm fine pixel pitch, 600-nit high brightness, 4,440Hz ultra-fast refresh rate, and 120% Rec.709 wide color gamut. Integrated ViewBoard® Cast screen sharing software* (along with optional ViewSonic vCastSender app), enables both on-site and online attendees to participate in video conferences and simultaneously share content. Equipped with twin dual-core processors, 4GB RAM, and 32GB of internal memory, the LD163-181 can play multimedia from internal storage or a USB flash drive 24 hours a day, seven days a week. And with remote configuration and content management system support, the ViewSonic LD163-181 is also suitable for a wide array of diverse signage applications.

 $\hbox{*Chrome, And roid, Windows, Mac OS, and iOS compliant}\\$



1. Menu Controls 2. Internal Speakers 3. HDMI 2.0 Out 4. USB 3.0 Type A (x1) 5. USB 2.0 Type A (x2) 6. RS232

24/7



7. HDMI 1.4 in (x2) 8. Audio Out 9. USB Type B 10. IR Receiver 11. LAN









Display:

Display Type: Direct View LED

Display Size (in.): 163 Viewable Area (in.): 163

Light Source: Fine Pixel Pitch LED

LED Pitch Size (mm): 1.875 LED Grayscale: 14 bits Resolution: 1920 x 1080 Refresh Rate (Hz): 4,440 Aspect Ratio: 16:9 Static Contrast Ratio: 6,000:1 Backlight Life (Hours): 100,000 Brightness: 600-nit

Viewing Angles: 160° horizontal, 160° vertical

Operation Rating: 24/7

Networking:

Wifi: 802.11ac (2.4GHz/5GHz)

Embedded Player:

OS: Android 8..0 Media Player Type: Yes

GPU: Mult-core MaliG51 MP2

Hi3751 V811 CPU: 4GB DDR4 Memory:

32GB (26GB available) Storage:

Audio:

Internal Speakers: 5W (x2)

Connector:

HDMI In(2), HDMI 1.4 Out (with HDCP 1.4)(1), HDMI 1.4 Out(1), 3.5mm Audio Out(1), USB 3.0(1), USB 2.0(2), USB 2.0 Type B(1), RS232(1), Ethernet LAN (RJ45)(1), IR in(1)

Power:

Voltage: 100-120V+/- 10%, 50/60Hz, 30A

Consumption (max): 2,660W 1,860W Consumption (typical): Stand-by: < 0.5 W

Controls:

On Screen Display: Yes Remote Control: Yes

Operating Conditions:

Temperature: 32-104° F (0 - 40° C)

Humidity (non-condensing): 20-80%

Weight (imperial):

Net (lbs): 423.3 Gross (lbs): 661.4

Weight (metric):

Net (kg): 192.0 Gross (kg): 300.0 Dimensions (imperial) (WxHxD):

Packaging (in.): 82.7 x 32.1 x 33.5 Physical (in.): 142.6 x 84.4 x 1.4

Dimensions (metric) (WxHxD):

Packaging (mm): 2100.0 x 815.0 x 850.0 Physical (mm): 3621.0 x 2143.5 x 35.0

General:

AV Control: AMX Certified, Crestron Certified, Extron Certified

Warranty: 5-year limited warranty on parts and labor, on-site service

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: Power Cord, Remote Control, QSG, Wall-mount x 1, Maintenance Tool (LD-MK-001) x 1, Spare Modules (LED PCB x 2)

Regulations: cTUVus, FCC, RoHS, Mexico CoC, Mexico Energy

UPC: 766907008791

Accessories:

LD-MK-001, LD-STND-002, NMP520-W, NMP520-WX, NMP660, SW-090, SW-091, SW-092, SW-093, SW-094, SW-095, SW-096, VB-CAM-001

Awards:





Copyright © ViewSonic Corporation 2000-2021. All rights reserved. (07/22/2021 12:46 AM PST)

Contact Us.

Ruko Sampoerna Square No.15, Jl. Raya Hankam, Jatiraden, Jatisampurna, Bekasi 17433 Telp. (021) 22813394 - info@mandiriarthasolusi.co.id - www.mandiriarthasolusi.co.id

Branch Office.

Ruko Derwati Mas Estate, No. 31, Jl. Derwati Raya, Kel. Derwati, Kec. Rancasari - Bandung 40292

Follow Us.





