

Interactive Flat Panel GALE Series



GALE Series Features



Android Versions

- Android 11.0
- 4Gb + 32Gb



Wireless Screen Sharing

- Support multiple devices Screenshare
- Support Android/Windows/MAC/Chrome OS
- Bidirectional connectivity



Zero Bonding Technology

- With Natural Writing Experience
- 0.5mm Zero bonding gap
- Improve wide display view & view-angle



Smart Pen Recognition

- Intelligent AI based writing prn
- Support



Improved Touch Accuracy and Efficiency

- Reduce parallax and improve touch accuracy
- 40 point touch (Windows)
- 20 point touch (Android)



Screen Splitting

- Two applications running on the screen at the same time.



Cloud Drive

- Support Google Drive & One Drive

GALE SERIES SPECIFICATION

Parameters	Size	GAH65LE	GA75LE	GA86LE	GA98LE	GA110LE
Display Parameters	BACK LIGHT	D-LED	D-LED	D-LED	D-LED	D-LED
	Display Area	1428.48*803.52mm	1649.74*927.94mm	1895.04*1065.96mm	2158.84*1214.35mm	2436.5*1370.5mm
	Resolution	3840x2160(pixels,RGB)				
	Contrast Ratio	1200: 1				
	Brightness	350cd/m²				
	Display Colors	1.07B(10bit)				
	Aspect Ratio	16:9				
	Response time	8ms (typ.)				
	Viewing Angle	178°(H) / 178°(V)				
	Led Life time	50,000 Hrs (min.)				
	Screen Protector	4mm Tempered AG Glass				
Audio	Speaker	8Ω , 15W x2				
Power Parameters	Power(No PC)	≤250W	≤350W	≤ 450W	≤ 450W	≤ 850W
	Working Voltage	100V~240V AC				
	Standby Power	≤ 0.5W				
AndroidOS	Android System	Android 11 (can upgrade to Android 13)				
	RAM and ROM	DDR4 4GB & EMMC 32GB				
	CPU /GPU	Quad Core, A55*4, 1.9Ghz GPU - Mali G52MP2				
	WIFI	802.11ac/b/g/n/a 2.4Ghz(Wi-Fi 5 or Wi-Fi 6 are optional) ; Hotspot 5Ghz +2.4Ghz				
	Bluetooth	Bluetooth 5.0				
	UI Resolution	4K				
	Ethernet network	10M/100M/1000M				
I/O Ports	Input	RJ45 IN*1; RS232*1; HDMI IN 2.0*2; VGA IN*1; VGA AUDIO IN *1; YPBPR IN *1 ; AV IN*1; MIC IN *1; USB 2.0*1; USB 3.0*2; TF/micro SD Card slot *1; DP 1.4*1; USB Type-C 2.0*1"				
	Output	"SPDIF OUT *1 ; AV OUT*1 ; AUDIO OUT*1; HDMI OUT 2.0*1; RJ45 OUT*1 ; Touch USB OUT 2.0*1;				
	Front Connection	HDMI IN 2.0*1; TOUCH USB OUT 2.0*1; USB Type-C 3.1 Gen1*1; USB 3.0 INPUT*3				
Touch Parameters	Touch Technology	Infrared technology (IR)				
	Touch Points	Windows system: 40 TOUCH; Android system: 20 TOUCH				
	Inductive objects	Finger or pen				
	Acuracy	Φ 1mm				
	Response time	≤6ms				
	Operation System	Support Windows, Mac, Android , Linux, Chrome				
Environment	Temperature	Working Temperature: 0°C ~ 45°C, Storage Temperature: -20°C ~ 60°C				
	Humidity	10% ~90%10% ~90%				
Packing Parameters	Physic Size	1490.6*904.8*88.95mm	1712.9*1030.9*89.15mm	1958.9*1169.75*89.15mm	2222.4*1322.65*106.1mm	2506.2*1484.3*106.1mm
	VESA Size	500*400mm	600*400mm	800*400mm	1000*400mm	1000*400mm
	Packaging Size	1576*980*200mm	1785*1125*200mm	2040*1260*200mm	2344*1458*240*mm	2665*1597*298*mm
	Net Weight	42±1 kg	54±1 kg	69±1 kg	80 ±1Kg	128 ±1Kg
	Gross Weight	56.5±1 kg	69±1 kg	83.8±1 kg	97 ±1Kg	153 ±1Kg
Standard Configuration	OPS slot	Slot supporting Standard OPS + OPS-C or slot supporting OPS-C Remote control* 1; Power cable 3M *1;				
	Accessories	Quick start guide ; Stylus Pen *2 ; Wall mounted bracket *1;				
Optional	Windows OPS	Windows10 i5 (8Gb/128Gb) / Windows10 i7 (16Gb/256Gb)				
	Speakers	20W x 2				
	Subwoofer	15W				
	Screen Share	Transcreen				
Warranty	Warranty	3 years warranty				

Office Address.

Head Office. Ruko Sampoerna Square No. 15, Jl. Raya Hankam, Jatisampurna – Bekasi 17433
Branch Office. Ruko Derwati Mas Estate No. 31, Jl. Raya Derwati, Rancasari – Bandung 40292

Follow Mandiri Artha Solusi on      

Contact us.

(021) 2281 3394 / Wha . 0812 1111 2948
info@mandiariarthasolusi.co.id
www.mandiariarthasolusi.co.id