

71.98.0396

D-CERNO DISCUSS D

D-Cerno Delegate Discussion Unit

CONFERENCE



Description

D-Cerno DISCUSS combines sleek design with advanced digital signal processing and true plug-and-play operation.

Stylish, discreet, and unobtrusive, the low-profile D-Cerno DISCUSS D blends seamlessly into any meeting room environment.

Built entirely on digital signal processing, the system delivers **crystal-clear audio** and outstanding speech intelligibility — two essential foundations for productive meetings.

In today's interconnected world, reliable communication is critical. That's why D-Cerno DISCUSS D features a shielded microphone that provides excellent **immunity to mobile phone interference**, allowing delegates to stay focused on what truly matters.

Designed for immediate use straight **out of the box**, D-Cerno DISCUSS D requires minimal technical expertise. Installation is simple: connect shielded Cat-5 cables from unit to unit. Thanks to **automatic signal-flow detection**, there's no need to worry about IN or OUT ports — cabling errors are virtually eliminated.

D-Cerno also offers exceptional flexibility. Expanding or reducing the number of units is quick and effortless, making the system particularly **well suited for rental applications**.

The D-Cerno DISCUSS D is compatible with **screw-lock D-MIC microphones**, available in different lengths.

Benefits

- » Modern, sleek, and contemporary design
- » Intuitive button layout with clear visual and tactile feedback
- » Removable microphone (not included) with different lengths available
- » Compact footprint and detachable microphone for easy transport and storage
- » Solid bottom housing for added weight, stability, and durability

Features

- » Digital signal processing for clear, intelligible audio
- » Shielded microphone providing immunity to mobile phone interference
- » High-quality integrated loudspeaker for natural sound reproduction
- » Integrated headphone output for private listening
- » Adjustable headphone volume control
- » Dedicated microphone On/Off button for intuitive operation
- » Loop-through, daisy-chain cabling for simple system wiring
- » Patented fail-safe redundancy for enhanced system reliability
- » Concealed conference bus connections for a clean, professional appearance
- » Bi-color bar indicator for clear status visibility
- » Microphone On/Off or Request-to-Speak push button with dual signaling LEDs

Connectivity

- » Two digital bus connections (IN/OUT - interchangeable)
- » Headphone connection:
TEL152 Headphones 71.04.0154
- » Screw-lock socket to connect a removable D-MIC microphone:
 - D-MIC 30 SL 71.98.0053
 - D-MIC 40 SL 71.98.0054
 - D-MIC 50 SL 71.98.0055
 - D-MIC 60 SL 71.98.0056
 - D-MIC 70 SL 71.98.0057
 - D-MIC 40 FF Full Flex 71.98.0059
 - D-MIC 40 BC Cardioid 71.98.0072
 - D-MIC 40 BC Hypercardioid 71.98.0073

Accessories

- » 2-m patch cable is included with the unit
- » D-Cerno transport case also available:
D-Cerno AE TC 71.98.0334



Certification



Region	Certification
Europe	CE

Specifications

Mechanical	
Material	PC/ABS & Zamak
Color	Black
Size	211.4 × 136 × 48.2 mm
Size packed	250 × 150 × 90 mm
Weight	780 g
Weight packed	1080 g
Electrical	
Power supply	48 DC, over Cat5e cable
Power consumption	2 W
Audio quality	24bit for microphone signal processing 16 bit for loudspeaker and headphone
Frequency response	25 Hz - 15,000 Hz (± 3 db)
Headphones	
Impedance	16-150 Ω
Output level	Max 70 mW 32 Ω
Speaker	
Rated power	4 W
Mean sound pressure level	80 dB SPL at 1m
Environment	
Operating temperature	5 to 45°C
Humidity	< 95%, >5%

Technical Drawings (mm)





Head Office.

Ruko Sampoerna Square No. 15 \ \ Jl. Raya Hankam, Jatiraden, Jatisampurna, Kota Bekasi 17436

Branch Office.

• **West Java**, Ruko Derwati Mas Estate, No. 31 \ \ Jl. Derwati Raya, Rancasari, Bandung 40292

• **Central Java**, Ruko San Fransisco, No. 17 \ \ Block F, Citra Grand, Sambiroto, Tembalang, Semarang 50276

✕ **LET'S CONNECT**



0812 1111 2948



@mandiriartha



Mandiri Artha Solusi